

Cargo Star

Innovation in Dry Freight Distribution



KIDRON...
THE
INNOVATORS



For Class
3, 4, 5, 6 & 7
Chassis

Cargo Star

Innovative solutions for efficient dry freight distribution

Cargo Star dry freight truck bodies deliver the optimum return on investment, combining rugged designs with an innovative approach to manufacturing and delivery. The result: cost effective dry freight distribution solutions armed with the designed-in advantages most sought by the world's leading leasing companies and small

fleet owners. Cargo Star represents a beneficial blend of Kidron's transportation industry leadership and Kidron's legendary quality and durability. Plus, by utilizing all of Kidron's strategically located manufacturing locations, Cargo Star production and delivery efficiency can bring additional benefits right to your bottom line.





Cargo Star Standard Advantages

- Choose configurations in popular sizes, ranging from 9 to 28 feet in length and interior cargo heights from 84 to 108 inches.
- Aluminum sheet and post skin construction features our .040 pre-painted white sheet, securely riveted at 2 inches on center. Five intermediate front posts, side posts are on 16-inch centers.
- FRP Exterior Panels
- Rounded aerodynamic front roof rail with either a 9-inch or 5-inch radius. Built-in corner lights are visible from either the front or sides.
- Heavy duty front aluminum corner posts protect the body from damage.
- Extruded aluminum top and bottom exterior rails deliver excellent strength and durability.
- Rugged rear frame is made from durable galvaneal steel to withstand abuse from dock loading. Stainless steel rear frame is optional.
- Anti-sag interior roof bows are made of rugged galvanized steel.



- Rugged standard wood flooring is 1 1/8-inch hardwood laminate. Or, choose wood or steel floor options.
- Optional 24-inch steel tread deck plate at the rear door protects the interior from pallet jack and fork lift loading and unloading.
- Three-inch I-beam cross members are set at 12-inch centers with gussets as standard. Other spacing available.
- Choose standard roll-up door or select from a range of popular options.





Other Popular Options

CARGO MOVEMENT

- Hydraulic liftgates
- Walk ramps
- Side doors
- Steel stirrup side door step
- Recessed side stairway

CARGO SECURITY AND PROTECTION

- Interior wear band
- Cargo control
- Hardwood cargo tie slats
- Plywood interior panels

OPERATOR EFFICIENCY

- Exterior grab handles
- Interior lighting
- Cargo bay lights

FLOOR ALTERNATIVES

- 1 3/8-inch laminated hardwood
- Welded steel tread plate

EXTERIOR

- Smooth FRP quick-clean surface to highlight signage
- Choose either 9-inch or 5-inch aerodynamic front corners, both equipped with modular, full-visibility lighting.
- LED lights

For a complete collection of options, or for special requests, please contact Kidron.

Bumper Options

- Rear impact
- Full width rear impact
- Rear impact with 6" or 10" oak filled dock extension
- Full width rear impact with 6" or 10" oak filled dock extension.
- Center step for rear impact bumper
- 12-inch full width step bumper with recessed tail lights
- Chicago Style Bumper
- Air flow

Door Options

REAR DOORS

- Full opening overhead rollup rear door
- 2 panel full opening rear door
- 1 panel rear part opening
- 2 panel rear part opening

SIDE DOORS

- 1 panel side door
- 2 panel side door



CARGO STAR TRUCK BODY SPECIFICATIONS

OUTSIDE DIMENSIONS		INSIDE DIMENSIONS			
Model	Actual Length	LENGTH		LENGTH-F.R.P.	
		Panel Doors	Roll-Up Doors	Panel Doors	Roll-Up Doors
9	9' 7-1/2"	9' 2"	9' 1-1/2"	9' 4"	9' 2-1/2"
10	10' 7-1/2"	10' 2"	10' 1-1/2"	10' 4"	10' 2-1/2"
12	12' 7-1/2"	12' 2"	12' 1-1/2"	12' 4"	12' 2-1/2"
14	14' 7-1/2"	14' 2"	14' 1-1/2"	14' 4"	14' 2-1/2"
16	16' 7-1/2"	16' 2"	16' 1-1/2"	16' 4"	16' 2-1/2"
16	18' 7-1/2"	18' 2"	18' 1-1/2"	18' 4"	18' 2-1/2"
20	20' 7-1/2"	20' 2"	20' 1-1/2"	20' 4"	20' 2-1/2"
22	22' 7-1/2"	22' 2"	22' 1-1/2"	22' 4"	22' 2-1/2"
24	24' 7-1/2"	24' 2"	24' 1-1/2"	24' 4"	24' 2-1/2"
26	26' 7-1/2"	26' 2"	26' 1-1/2"	26' 4"	26' 2-1/2"
28	28' 7-1/2"	28' 2"	28' 1-1/2"	28' 4"	28' 2-1/2"

Model	Outside Width	Inside Width	F.R.P. Inside Width	Outside Height	Inside Height	REAR PANEL OPENING PANEL DOORS			REAR FRAME OPENING PANEL ROLL-UP DOOR		
						Width	Sill to Header Height	Floor to Header Height	Width	Sill to Header Height	Floor to Header Height
Wide-84	96"	92"	*	91"	84"	87-1/4"	78-5/16"	78-5/16"	87-1/4"	78-5/16"	78-5/16"
Wide-90	96"	92"	*	97"	90"	87-1/4"	84-5/16"	84-5/16"	87-1/4"	84-5/16"	84-5/16"
Wide-96	96"	92"	*	103"	96"	87-1/4"	90-5/16"	90-5/16"	87-1/4"	90-5/16"	90-5/16"
Wide-102	96"	92"	*	109"	102"	87-1/4"	96-5/16"	96-5/16"	87-1/4"	96-5/16"	96-5/16"
Wide-108	96"	92"	*	115"	108"	87-1/4"	102-5/16"	102-5/16"	87-1/4"	102-5/16"	102-5/16"
E-Wide-84	102"	98"	*	91"	84"	93-1/4"	78-5/16"	78-5/16"	93-1/4"	78-5/16"	78-5/16"
E-Wide-90	102"	98"	*	97"	90"	93-1/4"	84-5/16"	84-5/16"	93-1/4"	84-5/16"	84-5/16"
E-Wide-96	102"	98"	*	103"	96"	93-1/4"	90-5/16"	90-5/16"	93-1/4"	90-5/16"	90-5/16"
E-Wide-102	102"	98"	*	109"	102"	93-1/4"	96-5/16"	96-5/16"	93-1/4"	96-5/16"	96-5/16"
E-Wide-108	102"	98"	*	115"	108"	93-1/4"	102-5/16"	102-5/16"	93-1/4"	102-5/16"	102-5/16"

NOTE: All dimensions are for standard dry wall bodies with 1-1/8" net flooring and 1/4" plywood on sides and front.
 * FRP Inside width depends on FRP thickness. For details, contact the factory.



T H E I N N O V A T O R S